

AERIAL WORK PLATFORM APPLICATIONS



Why Choose a Fullriver Premium AGM Battery?

Whether you're powering a scissor lift, cherry picker, or boom lift, the requirements from a battery are very similar. Long Life, ease of change and deep cycling are all imperative for these applications, and that's where Fullriver Battery comes in. Our Deep Cycle batteries are constructed using pure lead plates for stronger connections between cells and are housed in a solid epoxy-sealed ABS case so that you don't have to worry about dangerous or explosive off-gassing.

These features provide the means of maintaining peak capacity for longer periods between charges, delivering the highest total energy over the life of the batteries, and lowering operating costs. AWP's are often used in remote sites for extended periods where watering and maintenance are unheard of. Maintenance worries are a thing of the past with Fullriver Battery.



BUILT BETTER.

- ABS plastic is more rigid than PPE; does not bulge under normal operation.
- Rigid casing Epoxy sealed case increases PSI limits
- Pure lead allows for more efficient transfer of electricity during discharge and recharge; less energy lost to heat.
- Over partition welding (OPW) provides greater shock and vibration resistance

Specifications on back

Fullriver DC Series Premium Deep Cycle AGM Batteries

	DC MODEL	VOLTS	GROUP SIZE	RES. CAPACITY (min)		CYC. CAPACITY [AH]		CRANKING (Amps)		TERM.	DIMENSIONS (in/mm)			WEIGHT	
				@ 25 Amps	@ 75 Amps	@ 5hr Rate	@ 20hr Rate	CA @ 32°F	CCA @ 0°F	TYPE	LENGTH	WIDTH	TTL HEIGHT	(lb/kg)	
	6 VOLT I	BATTER	IES												
	DC224-6	6	GC2	441	113	179	224	1080	900	M8 + TP08	10.24 (260)	7.08 (180)	10.70 (272)**	67.9 (30.8)	
	DC250-6	6	GC2	531	135	204	250	1160	960	M8 + TP08	10.31 (262)	7.13 (181)	10.71 (272)**	78.9 (35.8)	
	DC335-6	6	902/J305	751	184	274	335	1560	1300	DT	11.61 (295)	7.01 (178)	14.41 (366)	104.7 (47.5)	
	DC400-6	6	903/L16	885	229	340	415	1800	1500	DT	11.61 (295)	7.05 (179)	16.69 (424)	124.6 (56.5)	
	12 VOLT BATTERIES														
	DC85-12	12	24	145	34	70	85	600	510	M8 + TP08	10.24 (260)	6.65 (169)	9.29 (236)**	56.0 (25.4)	
	DC105-12	12	27	175	43	86	105	820	680	M8 + TP08	12.07 (307)	6.65 (169)	9.29 (236)**	67.5 (30.6)	
	DC115-12	12	24	145	34	70	85	600	510	M8 + TP08	10.23 (260)	6.65 (169)	8.46 (215)**	73.2 (33.2)	
	DC140-12	12	DIN	260	62	115	140	950	795	M8 + TP08	13.43 (341)	6.77 (172)	11.14 (283)**	95.5 (43.3)	
	DC150-12	12	GC12	295	80	130	150	1050	900	M8 + TP08	12.87 (327)	7.17 (182)	10.75 (273)**	94.8 (43.0)	
	DC215-12	12	921/J185	420	110	172	215	1200	1000	DTW	15.00 (381)	7.01 (178)	14.65 (372)	132.3 (60.0)	

^{**} Brass SAE post is removable, reducing total height by 0.86"



AGM Perfected.

FULLRIVER BATTERIES ARE AVAILABLE THROUGH OUR NATIONWIDE NETWORK OF AUTHORIZED DEALERS AND INTERNATIONAL BRANCHES. FOR MORE INFO VISIT OUR WEBSITE OR CALL US TOLL FREE AT 800-522-8191 / 805-484-7900 (LOCAL).





