



PREMIUM DEEP CYCLE AGM BATTERIES

fullriverbattery.com

Why Choose a Fullriver Premium AGM Battery?

Today's maintenance applications demand a robust power source that will provide safe, dependable and worry-free operation. Fullriver's AGM technologies utilize the most modern design and manufacturing techniques for consistent quality and long-term durability. Our batteries never require watering, which not only saves time spent on labor-intensive upkeep procedures, but also eliminates the risk of damage from acid spills on floors and carpets. Plus, due to their sealed construction, they are non-gassing and are ideal for sensitive environments including hospitals, schools, and universities.

Having the right batteries for your floor cleaning machines can have a huge impact on your ROI. Fullriver Deep Cycle AGM batteries are designed to provide the means of maintaining peak capacity for longer periods between charges, delivering the highest total energy over the life of the batteries, and lowering operating costs. Make sure you're getting the biggest return on your battery investment and clean up with a Fullriver AGM battery.

BUILT BETTER.

- ABS plastic is more rigid than PPE; does not bulge under normal operation.
- Rigid casing - Epoxy sealed case increases PSI limits
- Pure lead allows for more efficient transfer of electricity during discharge and recharge; less energy lost to heat.
- Over partition welding (OPW) provides greater shock and vibration resistance



Specifications on back →

Fullriver DC Series Premium Deep Cycle AGM Batteries

| DC MODEL | VOLTS | GROUP SIZE | RES. CAPACITY (min) | | CYC. CAPACITY (AH) | | CRANKING (Amps) | | TERM. TYPE | DIMENSIONS (in/mm) | | | WEIGHT (lb/kg) |
|--------------------------|-------|------------|---------------------|-----------|--------------------|-------------|-----------------|-----------|------------|--------------------|------------|----------------|----------------|
| | | | @ 25 Amps | @ 75 Amps | @ 5hr Rate | @ 20hr Rate | CA @ 32°F | CCA @ 0°F | | LENGTH | WIDTH | TTL HEIGHT | |
| 6 VOLT BATTERIES | | | | | | | | | | | | | |
| DC224-6 | 6 | GC2 | 441 | 113 | 179 | 224 | 1080 | 900 | M8 + TP08 | 10.24 (260) | 7.08 (180) | 10.70 (272)** | 68.6 (31.1) |
| DC245-6 | 6 | DIN | 457 | 120 | 198 | 245 | 1120 | 930 | AP | 9.61 (244) | 7.48 (190) | 10.83 (275)** | 72.5 (32.9) |
| DC250-6 | 6 | GC2 | 531 | 135 | 204 | 250 | 1160 | 960 | M8 + TP08 | 10.31 (262) | 7.13 (181) | 10..71 (272)** | 78.9 (35.8) |
| DC335-6 | 6 | 102/J305 | 751 | 184 | 274 | 335 | 1560 | 1300 | DT | 11.61 (295) | 7.01 (178) | 14.41 (366)** | 104.7 (47.5) |
| DC400-6 | 6 | 903/L16 | 885 | 229 | 340 | 415 | 1800 | 1500 | DT | 11.61(295) | 7.05 (179) | 16.69 (424) | 124.6 (56.5) |
| 12 VOLT BATTERIES | | | | | | | | | | | | | |
| DC85-12 | 12 | 24 | 145 | 34 | 70 | 85 | 600 | 510 | M8 + TP08 | 10.24 (260) | 6.65 (169) | 9.29 (236)** | 56.0 (25.4) |
| DC105-12 | 12 | 27 | 175 | 43 | 86 | 105 | 820 | 680 | M8 + TP08 | 12.08 (307) | 6.65 (169) | 9.29 (236)** | 67.5 (30.6) |
| DC115-12 | 12 | 31 | 200 | 45 | 91 | 115 | 910 | 760 | M8 + TP08 | 12.91 (328) | 6.67 (172) | 4.44 (241)** | 73.2 (33.2) |
| DC140-12 | 12 | DIN | 260 | 62 | 115 | 140 | 950 | 795 | M8 + TP08 | 13.43 (341) | 6.77 (172) | 11.38 (289) | 95.0 (43.1) |
| DC150-12 | 12 | GC12 | 295 | 80 | 130 | 150 | 1050 | 900 | M8 + TP08 | 12.87 (327) | 7.17 (182) | 11.57 (294) | 95.5 (43.3) |
| DC215-12 | 12 | 921/J185 | 420 | 110 | 172 | 215 | 1200 | 1000 | DTW | 15.00 (381) | 7.01 (178) | 14.65 (372) | 132.3 (60.0) |

** Brass SAE post is removable, reducing total height by 0.86"



AGM Perfected.

FULLRIVER BATTERIES ARE AVAILABLE THROUGH OUR
NATIONWIDE NETWORK OF AUTHORIZED DEALERS
AND INTERNATIONAL BRANCHES. FOR MORE INFO
VISIT OUR WEBSITE OR CALL US TOLL FREE AT
800-522-8191 / 805-484-7900 (LOCAL).

fullriverbattery.com

