

### **JEEP APPLICATIONS**



#### Why Choose a Full Throttle Premium AGM Battery?

Full Throttle is a true dual-service battery equipped to handle the challenges presented in the backcountry. The TPPL (thin-plate, pure lead) grids provide a burst of energy on demand in hot or cold climates with rapid recharge once the alternator is spinning. The grids are heavily tinned allowing for use in light-duty cycling such as winching, navigation, lighting, and air systems. High compression cells connected with OTP (Over-The-Partition) technology ensure resilience when the road gets bumpy. The hassle-free, zero-spill technology allows for creative mounting, with no corrosion or dangerous gassing.

Our batteries provide high capacity and long cycle life of a true deep cycle battery with all the convenience and benefits of being maintenance-free. Full Throttle sets the standard for AGM in offroad vehicle applications. Whether in the wilderness or out on the road, rest assured your vehicle's uptime will be maximized for years to come when it's powered by a Full Throttle battery.



#### BUILT BETTER.

- ABS plastic is more rigid than PPE; does not bulge under normal operation.
- Rigid casing Epoxy sealed case increases PSI limits.
- Pure lead allows for more efficient transfer of electricity during discharge and recharge; less energy lost to heat.
- Over partition welding (OPW) provides greater shock and vibration resistance.

## **Full Throttle FT Series Premium High Cranking AGM Batteries**

FT MODEL	GROUP SIZE	CCA	PHCA	НСА	CA	CAP. C20 (AH)	RES. CAP. @ 25A (min)	POSITIVE TERM. POSITION	TERM. TYPE	DIMENSIONS (in / mm)				WEIGHT
										LENGTH	WIDTH	HEIGHT	TTL HEIGHT	(lbs / kg)
FT610-47	47/L2/H5	610	1280	890	745	50	105	RHP	AP	9.49 (241)	6.89 (175)	7.48 (190)	7.48 (190)	42.1 (19.1)
FT680-48	48/L3/H6	680	1320	975	810	60	120	RHP	AP	10.94 (278)	6.89 (175)	7.48 (190)	7.48 (190)	48.1 (21.8)
FT750-25	25	750	1400	1080	900	64	120	LHP	AP	9.45 (240)	6.85 (174)	7.95 (202)	8.66 (220)	49.2 (22.3)
FT750-35	35/34R	750	1400	1080	900	64	120	RHP	AP	9.45 (240)	6.85 (174)	7.95 (202)	8.66 (220)	49.2 (22.3)
FT825-34	34	825	1500	1200	1000	65	135	LHP	M8 + TP28	10.28 (261)	6.77 (172)	7.19 (182)	8.19 (208)**	46.1 (20.9)
FT825-78	34/78	825	1500	1200	1000	65	135	LHP	M8 + FR45	10.28 (261)	6.77 (172)	7.19 (182)	8.31 (211)	46.5 (21.1)
FT840-24M	24M	840	1650	1200	1050	75	163	LHP	DT	10.87 (276)	6.77 (172)	8.13 ( 207 )	8.95 (227)	54.0 (24.5)
FT840-24F	24F	840	1650	1200	1050	75	163	RHP	AP	10.87 (276)	6.77 (172)	8.13 ( 207 )	8.95 (227)	54.0 (24.5)
FT850-94R	94R/L4/H7	850	1888	1200	1070	85	175	RHP	AP	12.36 (314)	6.85 (174)	7.47 (190)	7.47 (190)	56.4 (25.6)
FT890-49	49/L5/H8	890	1800	1300	1070	80	168	RHP	AP	13.90 (353)	6.89 (175)	7.24 (184)	7.48 (190)	61.1 (27.7)
FT930-65	65	930	1750	1350	1070	75	142	LHP	M8 + TP28	11.81 (300)	7.17 (182)	6.65 (169)	7.24 (184)**	54.2 (24.6)

<sup>\*\*</sup> Brass SAE post is removable, reducing total height by 0.86"



# **START** YOUR **ADVENTURE**

FULLRIVER BATTERIES ARE AVAILABLE THROUGH OUR NATIONWIDE NETWORK OF AUTHORIZED DEALERS AND INTERNATIONAL BRANCHES. FOR MORE INFO VISIT OUR WEBSITE OR CALL US TOLL FREE AT 800-522-8191 / 805-484-7900 (LOCAL).





