



**DC220-6**  
GROUP GC2/GC2H

## PREMIUM DEEP CYCLE AGM BATTERIES

[fullriverbattery.com](http://fullriverbattery.com)

### Why Choose a Fullriver Premium AGM Battery?

Downtime on your machines means downtime for your business, which can cause headaches. Fullriver deep-cycle AGM batteries feature several design elements that provide optimum performance, while mitigating those downtime worries. The robust casing and higher valve settings extend the life cycle, while pure lead plates ensure high-power density and faster charging times. Our EGL and DC Series batteries are temperature tolerant, shock and vibration resistant, and have a low internal resistance for higher discharge current. All Fullriver batteries are spill proof, zero-watering, and no gassing, which means no maintenance or messy acid to cleanup and overall longer life.

Our batteries provide high capacity and long cycle life of a true deep cycle battery with all the convenience and benefits of being maintenance-free. Fullriver sets the standard for AGM in Industrial applications. Whether in the warehouse or out on the road, rest assured your fleet uptime will be maximized for years to come when it's powered by a Fullriver battery.



### BUILT BETTER.

- ABS plastic is more rigid than PPE; does not bulge under normal operation.
- Rigid casing - Epoxy sealed case increases PSI limits.
- Pure lead allows for more efficient transfer of electricity during discharge and recharge; less energy lost to heat.
- Over partition welding (OPW) provides greater shock and vibration resistance.

*Specifications on back* →

## Fullriver DC Series Premium Deep Cycle AGM Batteries

DC MODEL	VOLTS	GROUP SIZE	RES. CAPACITY (min)		CYC. CAPACITY (AH)		CRANKING (Amps)		TERM. TYPE	DIMENSIONS (in/mm)			WEIGHT (lb/kg)
			@ 25 Amps	@ 75 Amps	@ 5hr Rate	@ 20hr Rate	CA @ 32°F	CCA @ 0°F		LENGTH	WIDTH	TTL HEIGHT	
<b>6 VOLT BATTERIES</b>													
DC220-6	6	27	425	112	180	220	1170	990	M8	12.05 (306)	6.85 (174)	8.90 (226)**	72.1 (32.7)
DC224-6	6	GC2	441	113	179	224	1080	900	M8 + TPO8	10.24 (260)	7.08 (180)	10.70 (272)**	68.6 (31.1)
DC245-6	6	DIN	457	120	198	245	1120	930	AP	9.61 (244)	7.48 (190)	10.83 (275)**	72.5 (32.9)
DC250-6	6	GC2	531	135	204	250	1160	960	M8 + TPO8	10.31 (262)	7.13 (181)	10.71 (272)**	78.9 (35.8)
<b>12 VOLT BATTERIES</b>													
DC85-12	12	24	145	34	70	85	600	510	M8 + TPO8	10.24 (260)	6.65 (169)	9.29 (236)**	56.0 (25.4)

## Fullriver EGL Series Supreme Deep Cycle AGM Batteries

EGL MODEL	VOLTS	GROUP SIZE	RES. CAPACITY (min)		CYC. CAPACITY (AH)		CRANKING (Amps)		TERM. TYPE	DIMENSIONS (in/mm)			WEIGHT (lbs / kg)
			@ 25 Amps	@ 75 Amps	@ 5hr Rate	@ 20hr Rate	CA @ 32°F	CCA @ 0°F		LENGTH	WIDTH	TTL HEIGHT	
<b>6 VOLT BATTERIES</b>													
EGL200-6	6	GC2	375	100	155	200	1100	910	M8	10.24 (260)	7.13 (181)	10.33 (262)	74.1 (33.6)
EGL220-6	6	GC2/GC2H	470	118	180	220	1180	970	M8	10.31 (262)	7.13 (181)	11.06 (281)	82.7 (37.5)
EGL170-8	8	GC8	330	120*	140	170	1360	1100	M8	10.25 (260)	7.17 (182)	11.35 (288)	81.6 (37.0)
EGL100-12	12	31	175	43	82	100	930	775	M8	12.95 (329)	6.73 (171)	9.09 (231)	74.5 (33.8)

\*Reserve capacity (minutes) @ 56 Amps

\*\* Brass SAE post is removable, reducing total height by 0.86"



# ASK ABOUT OUR POWERVAULT

The Perfect Drop-in Solution for Electric Pallet Jacks.

# AGM Perfected.

FULLRIVER BATTERIES ARE AVAILABLE THROUGH OUR NATIONWIDE NETWORK OF AUTHORIZED DEALERS AND INTERNATIONAL BRANCHES. FOR MORE INFO VISIT OUR WEBSITE OR CALL US TOLL FREE AT 800-522-8191 / 805-484-7900 (LOCAL).

fullriverbattery.com

