



POWERVAULT

The **Fullriver PowerVault** is a maintenance-free battery pack like no other. Featured is the unparalleled quality of Fullriver DC Series 224ah batteries charged by the renowned Delta-Q IC650. These premium energy solutions are housed together in a highly adaptable shell to provide consistent power you can rely on.

PV224 SPECS

VOLTAGE

24 VOLTS

20 HOUR RATE

224 AH

5 HOUR RATE

179 AH

LENGTH

25 1/16" (636.6 mm)

WIDTH

7 1/2" (190.5 mm)

HEIGHT

24 1/2" (622.3 mm)

WEIGHT

329 lbs (149 kg)



MODEL
PV224

www.fullriverbattery.com

FEATURES & BENEFITS

SHELL / CASE

ROBUST AND COMPACT
POWDER-COATED STEEL SHELL

- Fits Raymond 102, Toyota HBW, Yale MPB, Hyster W45, Crown WP lifts, and more.
- Protective hinged cover.
- Secure battery hold-downs.
- Built-in lifters for easy movement and installation.
- Easy service access to all components.
- All components available separately (case, batteries, cables, and charger).

BATTERIES

PREMIUM AND MAINTENANCE-FREE,
FULLRIVER DEEP CYCLE AGM
BATTERIES

- ~25% more run time compared to common group 24/27 packs.
- Powered by four premium Fullriver GC Group batteries.
- Faster charging times than flooded and gel battery packs.
- Corrosion-free and maintenance-free AGM batteries.

CHARGER

AUTOMATIC AND FEATURE-RICH,
ON-BOARD DELTA-Q IC650 SMART
BATTERY CHARGER

- Precise charge algorithm designed and validated by Delta-Q and Fullriver.
- Temperature compensated charging ensures ideal power delivery in hot and cold environments maximizing battery life.
- Sealed IP66 rating protects from the elements.
- Low voltage pickup down to 1.2 volts.
- Data capture (up to 500 cycles) with easy reporting.
- Integrated LED and user display for charge status and program updates.
- CEC energy efficiency approved.
- Plug-in and charge any where there is a 120/240VAC outlet.

WARRANTY

INDUSTRY LEADING WARRANTIES
FOR INDUSTRY LEADING PRODUCTS

- 18 month replacement warranty for Fullriver batteries.
- 2 year replacement warranty for Delta-Q IC650 battery charger.

