



DC1150-2
GROUP L16



**PREMIUM DEEP CYCLE
AGM BATTERIES**

fullriverbattery.com

Why Choose a Fullriver Premium AGM Battery?

Off-grid and remote power setups have been growing over the years with the increasing popularity of creating clean, environmentally-friendly energy solutions. Fullriver Battery has been keeping up with the trend by constantly improving our battery technology to best fit specific applications. Our Deep Cycle AGM batteries are compatible with a wide-range of solar electricity systems, plus our dual top terminals provide greater installation flexibility, allowing for both recreational and industrial deep-discharge applications.

Creating and using renewable energy is a way of life and, at the end of their long life, Fullriver batteries are 99% recyclable. Using pure-lead, thick-plates, and a low rate of self-discharge, combined with zero watering, maintenance, or gassing makes Fullriver the perfect pairing for any solar application.



BUILT BETTER.

- ABS plastic is more rigid than PPE; does not bulge under normal operation.
- Rigid casing - Epoxy sealed case increases PSI limits.
- Pure lead allows for more efficient transfer of electricity during discharge and recharge; less energy lost to heat.
- Over partition welding (OPW) provides greater shock and vibration resistance.

Specifications on back →

Fullriver DC Series Premium Deep Cycle AGM Batteries

DC MODEL	VOLTS	GROUP SIZE	RES. CAPACITY [min]		CYC. CAPACITY [AH]		CRANKING [Amps]		TERM. TYPE	DIMENSIONS (in/mm)			WEIGHT [lb/kg]
			@ 25 Amps	@ 75 Amps	@ 5hr Rate	@ 20hr Rate	CA @ 32°F	CCA @ 0°F		LENGTH	WIDTH	TTL HEIGHT	
2 VOLT BATTERIES													
DC1150-2	2	L16	2235	658	945	220	5400	4500	M10	11.61 (295)	7.05 (179)	16.18 (411)**	127.0 (57.6)
6 VOLT BATTERIES													
DC224-6	6	GC2	441	113	179	224	1080	900	M8 + TP08	10.24 (260)	7.08 (180)	10.70 (272)**	68.6 (31.1)
DC250-6	6	GC2	531	135	204	250	1160	960	M8 + TP08	10.31 (262)	7.13 (181)	11.14 (283)**	78.9 (35.8)
DC335-6	6	902/J305	751	184	274	335	1560	1300	DT	11.61 (295)	7.00 (178)	14.37 (365)	104.7 (47.5)
DC400-6	6	903/L16	885	229	340	415	1800	1500	DT	11.61 (295)	7.05 (179)	16.69 (424)	124.6 (56.5)
12 VOLT BATTERIES													
DC85-12	12	24	145	34	70	85	600	510	M8 + TP08	10.24 (260)	6.65 (169)	9.29 (236)**	56.0 (25.4)
DC105-12	12	27	175	43	86	105	820	680	M8 + TP08	12.07 (307)	6.65 (169)	9.29 (236)**	67.5 (30.6)
DC115-12	12	31	200	45	91	115	910	760	M8 + TP08	12.91 (328)	6.77 (172)	9.49 (241)**	73.2 (33.2)
DC140-12	12	DIN	260	62	115	140	950	795	M8 + TP08	13.43 (341)	6.77 (172)	11.38 (289)**	95.0 (43.1)
DC215-12	12	921/J185	420	110	172	215	1200	1000	DTW	15.00 (381)	7.01 (178)	14.65 (372)	132.3 (60.0)
DC260-12	12	8D	578	145	214	260	1830	1525	LT / APW	20.51 (521)	10.59 (269)	9.65 (245)	173.3 (78.6)

** Brass SAE post is removable, reducing total height by 0.86"



AGM Perfected.

FULLRIVER BATTERIES ARE AVAILABLE THROUGH OUR
NATIONWIDE NETWORK OF AUTHORIZED DEALERS
AND INTERNATIONAL BRANCHES. FOR MORE INFO
VISIT OUR WEBSITE OR CALL US TOLL FREE AT
800-522-8191 / 805-484-7900 (LOCAL).

fullriverbattery.com

